

Special For DC-AC Rectifier Bridge

Features

- Compliant with RoHS Provisions
- Low forward voltage, high forward current
- High forward surge current capability
- High heat-conducting performance
- Thermal welding performance:
260 °C/10sec

Applications

- Switching Power Supply
- Home Appliances, Office Devices
- Industrial Auto-equipments

Input Pin (~)	
Input Pin (~)	
Output (+)	
Output (-)	

	V_{RRM}		V
Maximum RMS voltage	V_{RMS}		V
Maximum DC Blocking Voltage	V_{DC}		V
Average Rectified Output Current	I_o	10.0	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load(JEDEC Method)	I_{FSM}	200	A
$I^2 t$ rating for fusing (1ms < t < 8.3 ms)			
Maximum Forward Voltage at 5.0 A	V_F	1.25	V
			μA
Junction to ambient without heatsink Junction to case, with heatsink			
Operating and Storage Temperature Range	T_j, T_{stg}	-55 ~ +150	°C

RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)

Fig.1: Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3: Max. Surge Current




Fig.4: Rated Forward Features

Forward Current IF A


Cycles Number (cycle)

Forward Voltage VF V



PACKAGE OUTLINE DIMENSIONS


Note:unit mm(inch)



GBU mechanical data: unit mm(inch)

Unit		A	B	C	D	E	F	H	J	K	L	M	N
mm	max	22.3	4.1	18.8	18.5	2.1	5.43	1.15	2.24	5.6	3.6	2.3	0.6
	min	21.7	3.5	18.2	17.5	1.5	4.73	0.85	1.64	5.1	3.2	1.8	0.4
inch	max	0.88	0.17	0.74	0.73	0.09	0.22	0.045	0.09	0.22	0.15	0.09	0.03
	min	0.85	0.13	0.71	0.68	0.06	0.18	0.033	0.06	0.20	0.12	0.07	0.015

Marking Information



W : Company's trademark
GB

